

400V APTITUDE OPEN FRONT STUDENT DESK

usacapitol

PREMIUM QUALITY CLASSROOM FURNITURE



DESK FEATURES

- Plateable-quality heavy-gauge steel • 5/8" warp-free top • Book boxes reinforced with a steel rod • High-quality chrome inserts • Long-ferrule inside holding nylon glides • Through-screw plastic attachment
- Superior extra-long frame welds • available in colors to complement stock chair colors
- Steel glides • Perforated Bookbox

OPTIONS

- Steel glides • Perforated Bookbox

Aptitude™ 400V Open Front Student Desk Specifications

Frame: 1-1/8" diameter, 18-gauge legs are robotically welded together with two brackets of 13-gauge die-formed steel, integrally tying all tube parts for maximum structural integrity. Minimum 12" inches of total weld. Frame made entirely with colled-rolled, plateable quality steel insuring a quality finish application.

Standard Frame Finishes:

Electrostatically applied powdercoated Minitex Black is standard. Minitex Navy, and Hammered Silver are optional unit colors. (Other optional colors available with require an upcharge)

Inserts: .995" diameter, nickel/chrome plated 16ga tubing with punched holes to receive adjusting screws. Leg adjustment uses self-tapping locking screws which pass completely through both upper leg and lower insert. Chrome is comprised of metal layers (Nickel & Chromium) electrostatically bonded to metal. Our standard is 4-6 mills (25%-50% more than our competitors) of Nickel—it will not scratch. Our product is chromed on plateable quality tubing after all welding is completed to prevent rusting on unfinished welds.

Bookbox: Open front: 4-1/2" x 22" x 15" deep, 20-gauge, One Piece, seamless, deep drawn steel box. Die formed pencil groove. Embossed for minimum vibration and maximum strength.

Glides: Glide base material will be thermomolded from synthesized hybrid copolymers. Glide attachment will be a standard internal gripping spring steel umbrella at least 5/8" diameter or larger. The glide will have a

ferrule. Glide casing and ferrule shall be constructed of durable case hardened steel; no plastic. The glide will be of full swivel design, silent and firm fitting for positive attachment and retention. All glides must make full level contact with the floor and the maximum swivel angle of the glide shall not be violated. All glides must be factory installed and permanently attached.

Top: Solid molded thermoset plastic. 18" x 24" x 5/8" with smooth molded edges and permanent color throughout thickness. Pencil groove. Top is attached using self-tapping screws into seven uniformly drilled holes.

Top Colors: Available in standard Beige and Grey. Optional Grey Nebula, Charcoal, Maple, Oak, Cherry, Walnut, and Mahogany available with upcharge.

Warranty:

- Limited lifetime frame warranty
- 10 Year Comprehensive Warranty

Cartons: Shipped two per carton.

Models:

400V • 22"-32" Adjustable at 1" Increments.



Optional Hard Plastic Top Colors: Grey Nebula, Charcoal, Maple, Oak, Cherry, Walnut, and Mahogany.

