

439P/430P APTITUDE STUDENT DESKS

usacapitol
PREMIUM QUALITY CLASSROOM FURNITURE



Simplicity & Utility. 20% more work surface (510 square inches total). The best of both worlds is exemplified in this utilitarian dream. Function and form are exemplified in this attractive student desk.

H I G H L I G H T E S



439P



D E S K F E A T U R E S

- Safe, bracketless continuous all-tubular frame
- Heavy-Duty inserted U-brace support
- Plateable-quality heavy-gauge steel
- 5/8" warp-free top with pencil groove
- High-quality chrome inserts
- Patented Capitol Express™ Glides
- Superior extra-long frame welds
- Locking-screw insert attachment

- Available in colors to complement stock chair colors

O P T I O N S


- Adjustable or fixed height models
- Powder coated frame



Standard Frame
Color: CHROME



Standard Hard Plastic Top
Colors: Sand and Slate



Optional Hard Plastic Top Colors:
Grey Nebula, Charcoal, Maple, Oak, Cherry, Walnut, and Mahogany.

- Premium Quality
- Welded U-brace
- 18 Gauge Legs
- Welded Under Structure
- Lifetime Frame Warranty
- Adjustable or Fixed Height
- 2 Standard Top Colors
- 7 Optional Top Colors

Aptitude™ 439P Student Desk Specifications

Frame: All-tubular design, 1" diameter, 18-gauge front leg running from side to side is multiple arc welded to an integral 1", 18-gauge U-shaped top support and rear leg. 5/8", 16 gauge tubular U-brace is inserted into punched holes in the rear legs and welded to all four legs. Minimum 4-1/2" of total weld. Frame is chrome plated after all welding is complete.

Standard Chrome Finish:

Chrome is comprised of metal layers (Nickel & Chromium) electrostatically bonded to metal. Our standard is 4-6 mills (25%-50% more than our competitors) of Nickel-it will not scratch. Our product is chromed on plateable quality tubing after all welding is completed to prevent rusting on unfinished welds.

Inserts: 86" diameter, nickel/chrome plated tubing with punched holes to receive adjusting screws. Leg adjustment uses self-tapping locking screws which pass completely through both upper leg and lower insert.

Glides: Glides shall be Capitol Express™ VCT non-marring floor glides or pre-approved equal; no exceptions. Radius base glide designs are not acceptable. Glide base material will be thermo-molded from synthesized hybrid copolymers. Glide material must not retain dirt or grit. Glide attachment will be a standard internal gripping spring steel umbrella at least 5/8" diameter or larger. The glide will have a

ferrule. Glide casing and ferrule shall be constructed of durable case hardened steel; no plastic. The glide will be of full swivel design, silent and firm fitting for positive attachment and retention. All glides must make full level contact with the floor and the maximum swivel angle of the glide shall not be violated. All glides must be factory installed and permanently attached. Non permanent after market glide caps can be hazardous when detached and will not be considered.

Top: Solid molded thermoset plastic. 19" x 26" work surface with smooth molded edges and permanent color throughout thickness. Molded pencil groove. Top is attached using self-tapping screws into seven uniformly drilled holes.

Top Colors: Available in standard Sand and Slate. Optional Charcoal, Grey Nebula, Maple, Oak, Cherry, Mahogany, and Walnut

Warranty:

- Limited lifetime frame warranty
- Ten Year Comprehensive

Samples: Compliance with the specifications and verification of required quality levels may be determined by requesting samples.

Models:

- **430P** ♦ 23-1/2" to 29-1/2" Adjustable.
- **439P** ♦ 29-1/2" Fixed Height.



430P
Adjustable height.

